

## Product Information

## BREAK-THRU® OE 446

## PRODUCT DESCRIPTION

BREAK-THRU® OE 446 is a polyether polysiloxane.

## Typical Properties

Property	Unit	Value
<b>Color</b>		yellowish
<b>Density</b>	g/cm <sup>3</sup>	1.04-1.06 at 25°C
<b>Flash Point, min.</b>	°C	90
<b>Solubility</b>		soluble in Butanol at 10%
<b>Solubility</b>		soluble in Cyclohexanone at 10%
<b>Solubility</b>		dispersible in Isopar™ M
<b>Solubility</b>		soluble in NMP at 10%
<b>Solubility</b>		soluble in Rapeseed Methylester at 10%
<b>Solubility</b>		soluble in Solvesso™ 150 at 10%
<b>Solubility</b>		dispersible in Sunflower Oils at 10%
<b>Solubility</b>		soluble in Water at 10%
<b>Viscosity</b>	mPa·s	800-1100 at 25°C

The data represents typical values (no product specification)

## TYPICAL APPLICATIONS

As additive for in-can formulations, BREAK-THRU® OE 446 can improve the performance and stability of oil-based pesticide formulations. Because of its water solubility,

BREAK-THRU® OE 446 is also suitable for aqueous based formulations such as SC, SL, EW, and SE.

BREAK-THRU® OE 446 leads to enhanced oil spreading as a consequence of lowering its surface tension.

BREAK-THRU® OE 446 generates nearly mono-molecular layers on solid surfaces which inhibit crystallisation of active ingredients and the agglomeration of solid particles in EC, OD and SC formulations. BREAK-THRU® OE 446 reduces abrasion and dust creation in seed treatments and in WDG formulations. BREAK-THRU® OE 446 can be diluted with water and sprayed on solid surfaces.

For dust reduction in seed treatment the use rate is 20-40 ml in 100 kg seeds.

## Product Composition

Product Composition	Unit	Value
<b>Active Content</b>	wt%	100

The data represents typical values (no product specification)

## BENEFITS &amp; ADVANTAGES

BREAK-THRU® OE 446

- Is oil and water soluble, making it suitable for oil-based and aqueous based formulations
- Has a wide range of pH stability, from 3-11, for flexible formulating
- Enhances the spreading of oils through a reduction in surface tension
- Provides increased stability, especially for OD formulations and reduces dust off in seed treatment
- The reduction in surface tension results in a "film building" property which helps to inhibit crystallization in EC, OD and SC formulations

## DOSAGE

100 ml/ha with pre-emergence herbicides.

50 ml/ha with all other systemic crop protection ingredients.

These rates refer to both tank mix and in-can applications.

20-150 ml/t for dust control and reduction of abrasion in seed treatment and WDG formulations.

## HANDLING & PROCESSING

### pH Stability

The stability of BREAK-THRU® OE 446 in aqueous solutions at pH values range of 3-11.

It can be reasonably assumed that BREAK-THRU® OE 446 is stable in aqueous solutions in the pH range of 3-11.

## PACKAGING

4 x 210 kg drums (full pallet)

1000 kg plastic containers

## SHELF LIFE

BREAK-THRU® OE 446 is stable in closed containers for 2 years. BREAK-THRU® OE 446 is not sensitive to freezing.

## HAZARDOUS SUBSTANCE

Information concerning

- Classification and labelling according to regulations for transport and for dangerous substances
- Protective measures for storage and handling
- Measures in case of accidents and fire
- Toxicity and ecological effects

is given in our material safety data sheets.

## REGISTRATION LISTING SUMMARY

Per 40 CFR 180.910, BREAK-THRU® OE 446 is exempt from the requirement of a tolerance.

BREAK-THRU® OE 446 is OMRI (Organic Materials Review Institute) listed.

The relevant components of BREAK-THRU® OE 446 are listed/registered or exempt in the following chemical inventories:

Registration Listings	
Registry	Status
<b>Australia (AICIS)</b>	Yes
<b>Canada (DSL)</b>	Yes
<b>China (IECSC)</b>	Yes
<b>European Union (EINECS/ELINCS)</b>	Yes
<b>Japan (ENCS)</b>	Yes
<b>Korea (KECL)</b>	Yes
<b>Philippines (PICCS)</b>	Yes
<b>United States of America (TSCA)</b>	Yes

### Disclaimer

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third-party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

### Evonik Operations GmbH

Interface & Performance  
Goldschmidtstraße 100  
45127 Essen, Germany  
Phone Europe +49 201 173-2665  
Phone Asia +86 21 61191 125  
Phone Americas +1 804 727 0700  
interface-performance@evonik.com  
[evonik.click/interface-performance](http://evonik.click/interface-performance)