

## Product Information

## TEGO® Antifoam MR 507

## PRODUCT DESCRIPTION

TEGO® Antifoam MR 507 is an antifoam based on organo-modified siloxanes for foam control in non-aqueous media.

## Typical Properties

Property	Unit	Value
<b>Appearance</b>		Yellowish to brownish liquid
<b>Density</b> at 25°C	g/cm <sup>3</sup>	1.00
<b>Solvent</b>		Aromatic hydrocarbon
<b>Viscosity</b> at 25°C	mPa·s	500-1500

The data represents typical values (no product specification)

## TYPICAL APPLICATIONS

TEGO® Antifoam MR 507 is used as an antifoam for diesel additive packages or diesel fuels. Our product can especially be used for diesel fuels with high amounts and different sources of bio components.

## Product Composition

Product Composition	Unit	Value
<b>Active Content</b>	wt%	78-82
<b>Silicone Rubber Content</b>	wt%	9.0-11.0

The data represents typical values (no product specification)

## BENEFITS &amp; ADVANTAGES

Due to the high silicone content of TEGO® Antifoam MR 507 it outperforms conventional products in bio treated diesel fuels regarding following points.

## Efficiency in dry and wet fuel

TEGO® Antifoam MR 507 reduces substantially and reliably both, foam collapse time and initial foam height. It

maintains its outstanding performance even in wet fuel and after a storage time of the treated fuel exceeding 4 weeks.

## Water shedding properties


Excellent water shedding properties could be achieved by using a sulphur-free demulsifier.

## Reduced treat rate

Compared to conventional antifoams based on polyether siloxanes, TEGO® Antifoam MR 507 proved to be much more efficient resulting in strongly reduced treat rates.

## Compatibility in additive packages

TEGO® Antifoam MR 507 may be incorporated into diesel additive packages requiring only small amounts or even no additional use of solvents, i. e. TEGO® Antifoam MR 507 supports the formulation of low-solvent additive packages. It shows excellent compatibility with a wide range of packages, regardless the solvent base, detergents, etc. TEGO® Antifoam MR 507 can be incorporated in most additive packages yielding clear and stable formulations even at temperatures as low as -20°C. If solvents have to be used conventional non-polar types (e.g. aromatic hydrocarbons) may be used.



## DOSAGE

Depending on the composition of the additive package and the fuel grade the dosage of TEGO® Antifoam MR 507 may vary over a wide range. Consequently, the optimum dosage has to be evaluated in suitable test series. For first trials we recommend a dosage of 8 to 12 ppm referred to the treated fuel.

This dose rate should also be used in the case of solely adding the antifoam to the diesel fuel.

## HANDLING & PROCESSING

TEGO® Antifoam MR 507 is soluble in a variety of aromatic and aliphatic solvents (e.g. long chain alcohols). This provides maximum flexibility in the formulation of diesel additive packages. Examples of suitable solvents for TEGO® Antifoam MR 507 include

- Aromatic naphtha
- Toluene
- Isodecanol
- 2-ethylhexanol
- Hexanol
- Ethanol

## PACKAGING

950 kg containers

## STORAGE

In original closed containers TEGO® Antifoam MR 507 can be stored at room temperatures for at least 2 years.

## HAZARDOUS SUBSTANCE

Information concerning

- Classification and labelling according to regulations for transport and for dangerous substances
- Protective measures for storage and handling
- Measures in case of accidents and fire
- Toxicity and ecological effects

is given in our material safety data sheets.

## REGISTRATION LISTING SUMMARY

The relevant components of TEGO® Antifoam MR 507 are listed/registered or exempt in the following chemical inventories:

Registration Listings	
Registry	Status
<b>Australia (AICIS)</b>	Yes
<b>Canada (DSL)</b>	Yes
<b>European Union (EINECS/ELINCS)</b>	Yes
<b>Japan (ENCS)</b>	Yes
<b>Korea (TCCL)</b>	Yes
<b>Korea (KECL)</b>	Yes
<b>Philippines (PICCS)</b>	Exempted
<b>Türkiye (KKDIK)</b>	Yes
<b>Taiwan (TCSI)</b>	Yes
<b>United States of America (TSCA)</b>	Yes

### Disclaimer

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third-party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

### Evonik Operations GmbH

Interface & Performance  
Goldschmidtstraße 100  
45127 Essen, Germany  
Phone Europe +49 201 173-2665  
Phone Asia +86 21 61191 125  
Phone Americas +1 804 727 0700  
interface-performance@evonik.com  
[evonik.click/interface-performance](http://evonik.click/interface-performance)