

## Product Information

## TEGO® Antifoam MR 558

## PRODUCT DESCRIPTION

TEGO® Antifoam MR 558 is an antifoam based on organo-modified siloxanes for foam control in non-aqueous media.

## Typical Properties

Property	Unit	Value
<b>Appearance</b>		brownish liquid
<b>Density</b> at 25°C	g/ml	0.98
<b>Solvent</b>		Higher alcohols
<b>Viscosity</b> at 25°C	mPa·s	500-1250

The data represents typical values (no product specification)

## TYPICAL APPLICATIONS

TEGO® Antifoam MR 558 is used as an antifoam for diesel additive packages or diesel fuels. This product is designed for all kinds of diesel fuels, including those with high amounts and different sources of bio components.

## Product Composition

Product Composition	Unit	Value
<b>Active Content</b>	%	80
<b>Silicon (Si) Content, max.</b>	%	15

The data represents typical values (no product specification)

## BENEFITS &amp; ADVANTAGES

Due to the very high silicone content of TEGO® Antifoam MR 558 it outperforms conventional products in diesel fuels regarding the following points.

## Efficiency in dry and wet fuel

TEGO® Antifoam MR 558 reduces substantially and reliably both foam collapse time and initial foam height. It

maintains its outstanding performance even in wet fuel and after a storage time of the treated fuel exceeding 4 weeks.

## Water shedding properties

Excellent water shedding properties could be achieved by using a sulphur-free demulsifier.

## Reduced treat rate

Compared to conventional antifoams based on polyether siloxanes, TEGO® Antifoam MR 558 proved to be much more efficient resulting in strongly reduced treat rates.

## Compatibility in additive packages

TEGO® Antifoam MR 558 may be incorporated into diesel additive packages requiring only small amounts or even no additional use of solvents, i.e. TEGO® Antifoam MR 558 supports the formulation of low-solvent additive packages. It shows excellent compatibility with a wide range of packages, regardless the solvent base, detergents, etc. TEGO® Antifoam MR 558 can be incorporated in most additive packages yielding clear and stable formulations even at temperatures as low as -20°C.

## Low cyclic content

A key advantage of TEGO® Antifoam MR 558 is the low content of cyclic oligosiloxanes, well below the 0.1% threshold outlined by ECHA.

## DOSAGE

Depending on the composition of the additive package and the fuel grade the dosage of TEGO® Antifoam MR 558 may vary over a wide range. Consequently, the optimum dosage has to be evaluated in suitable test series. For first trials we recommend a dosage of 5 to 12 ppm referred to the treated fuel.

This dose rate should also be used in the case of solely adding the antifoam to the diesel fuel.

## HANDLING &amp; PROCESSING

TEGO® Antifoam MR 558 is soluble in a variety of aromatic and aliphatic solvents (e.g. long chain alcohols). This provides maximum flexibility in the formulation of diesel additive packages. Examples of suitable solvents for

TEGO® Antifoam MR 558 include: aromatic naphtha, toluene, isodecanol, 2-ethylhexanol, hexanol and ethanol.

## PACKAGING

Available in 950 kg IBCs

## STORAGE

In original closed containers TEGO® Antifoam MR 558 can be stored at room temperatures for at least 1 year.

## HAZARDOUS SUBSTANCE

Information concerning

- Classification and labelling according to regulations for transport and for dangerous substances
- Protective measures for storage and handling
- Measures in case of accidents and fire
- Toxicity and ecological effects

is given in our material safety data sheets.

## REGISTRATION LISTING SUMMARY

The relevant components of TEGO® Antifoam MR 558 are listed/registered or exempt in the following chemical inventories:

Registration Listings	
Registry	Status
European Union (EINECS/ELINCS)	Yes
United States of America (TSCA)	Yes

### Disclaimer

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third-party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

### Evonik Operations GmbH

Interface & Performance  
Goldschmidtstraße 100  
45127 Essen, Germany  
Phone Europe +49 201 173-2665  
Phone Asia +86 21 61191 125  
Phone Americas +1 804 727 0700  
interface-performance@evonik.com  
[evonik.click/interface-performance](http://evonik.click/interface-performance)